

PTFE - Folie (Teflon®) beschichtetes Glasgewebe nichtklebende Ausführung, als Meterware



Product	Product category	Coating
PLOFLON PTFE GLASS FABRIC non adhesive	Premium Serie	PTFE

These PLOFLON products provide a superior non-stick surface to achieve performance in a wide variety of applications with lower cost.

These products can be used in direct contact with food.

Properties	Value	Unit
Standard width Please ask for other widths	1000, 1500,	mm
Backing thickness	0,125 / 0,140 / 0,230, 0,330	mm
Weight	255 / 296 / 490 / 650	gr/m2
PTFE content	58 / 63 / 59 / 55	%
Tensile strenght	1200 / 1200 / 2300 / 3500	N/5 cm
Temperature resistance	-150° / +260°	Celsius
Roll standard length:	30	m
Backing thickness 0,125mm 0,140mm 0,230mm 0,330mm	Available in the following standard widths: 1000mm, 1250mm, 1500mm, 2000mm 1000mm, 1500mm 1000mm, 1500mm 1000mm, 1500mm, 2000mm, 2600mm, 3500mm	

Note:Nominal thickness, weight and tensile strenght values are typical and are not intended as a specification minimum.Weight Tolerance g/m² = ±%5

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON believes to be reliable, but they are not to be constured in any manner as warranties expressed.

All data is subject to change without notice.