## PLOFLON silicone rubber, extremely massive heat-resistant type.



## Product

Product category

Coating

PLOFLON silicone rubber, extremely massive heat-resistant type.

Premium Serie

Proportio

not adhesive

Applications: windows and cabin doors of airplanes, shaft seals, O-rings, safety mats, medical articles, electrical insulators, seals for refrigerators, ovens, drying cabinets.

value	Onit
834	mm
1200	mm
1,0 / 1,5 / 2,0 / 3,0 / 4,0 / 5,0 / 6,0	mm
very smooth surface	
not adhesive	N/cm
-60° / +220°	Celsius
Depending on the material thickness in rolls or in the form of sheet goods.	
	834 1200 1,0/1,5/2,0/3,0/4,0/5,0/6,0 very smooth surface not adhesive $-60^{\circ}/+220^{\circ}$ Depending on the material thickness in rolls or in the form of

Valu

Note:Nominal thickness, weight and tensile strenght values are typical and are not intended as a specification minimum. Weight Tolerance g/m<sup>2</sup> = ±%5

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON believes to be reliable, but they are not to be constured in any manner as warranties expressed.

All data is subject to change without notice.