PLOFLON Teflon film - adhesive with silicone adhesive SW10007



Product	Product category	Coating
PLOFLON PTFE GLASS FABRIC Self adhesive	Premium Serie	Silicone PSA

PLOFLON Premium Series PTEE/glass fabrics coated on one side with high temperature pressure sensitive silicone adhesive. Yellow textured PVC release liner is applied to the adhesive surface for ease of application.

Some application: Easy release surface on heat sealing and packaging machines, ironing and pressing equipment, covering drying cylinders, lining chutes, release surface on bonding tools.

Properties	Value	Unit
Standard width Please ask for other widths	1000, 1500,	mm
Backing thickness	Width 1000mm: 0,075, 0,125 / 0,140. 0,230, 0,330 Width 1500mm: 0,125 / 0,140	mm
Total thickness	Width 1000mm: 0,125, 0,175 / 0,190, 0,280, 0,380 Width 1500mm: 0,175 / 0,190	mm
Backing weight	135 / 255 / 296 / 455 / 650	gr/m2
Adhesion	5,40	N/cm
Temperature resistance	-73° / +260°	Celsius
Roll length:	from 1 m to 30 m Standard roll length 30 m	m

Note:Nominal thickness, weight and tensile strenght values are typical and are not intended as a specification minimum.Weight Tolerance g/m² = ±%5

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON believes to be reliable, but they are not to be constured in any manner as warranties expressed.

All data is subject to change without notice.