## PLOFLON Teflon Klebeband mit Silikonkleber SW10003



Product	Product category	Coating
Floudet	Froduct category	Coating

PLOFLON PTFE GLASS FABRIC Self adhesive

Premium Serie

Silicone PSA

Email: info@wbdatentechnik.de

Internet: http://www.ploflon.biz

PLOFLON Premium Series
PTFE/glass fabrics coated on one side
with high temperature pressure
sensitive silicone adhesive. Yellow
textured PVC release liner is applied to
the adhesive surface for ease of
application.

Some application: Easy release surface on heat sealing and packaging machines, ironing and pressing equipment, covering drying cylinders, lining chutes, release surface on bonding tools.

Properties	Value	Unit
Standard width Please ask for other widths	10, 20, 30, 40, 50, 100, 150, 300, 400, 500, 600,	mm
Backing thickness	0,125 / 0,140 / 0,240	mm
Total thickness	0,175 / 0,190 / 0,290	mm
Backing weight	255 / 296 / 490	gr/m2
Adhesion	5,40	N/cm
Temperature resistance	-73° / +260°	Celsius
Roll length:	30	m

Note: Nominal thickness, weight and tensile strenght values are typical and are not intended as a specification minimum. Weight Tolerance g/m² = ±%5

Tel.: +49 2331 7884618

Fax.: +49 2331 7874017

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON believes to be reliable, but they are not to be constured in any manner as warranties expressed.

All data is subject to change without notice.