## PLOFLON Teflon film, self-adhesive, round circle made



Product	Product category	Coating
PLOFLON PTFE GLASS FABRIC Self adhesive	Premium Serie	Silicone PSA

PLOFLON Premium Series PTFE skived film with one side coated with a pressure sensitive silicone adhesive.

Good strength, abrasion resistance and the low friction properties of Skived PTFE film make it a prime choice for mechanical applications from lining guide rails to wrapping wire harnesses.

For mechanical applications and all-purpose use, PTFE tape offers superior low friction and non-stick properties.

Please indicate required liner to your order one

- Corrugated Yellow Liner
  Flat Transparent Liner

Properties	Value	Unit
Diameter Please ask for other diameters	19 / 20 / 50 / 100	mm
Backing thickness	0,530	mm
Total thickness	0,600	mm
Adhesion	6,30	N/cm
Temperature resistance	-73° / +260°	Celsius

Email: info@wbdatentechnik.de

Internet: http://www.ploflon.biz

Note: Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m² = ±%5

Tel.: +49 2331 7884618

Fax.: +49 2331 7874017

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON believes to be reliable, but they are not to be constured in any manner as warranties expressed.

All data is subject to change without notice.