

# PLOFLON PTFE- Teflon Schlauch – hitzebeständig, antihaftend, reißfest



| Product                   | Product category      | Coating |
|---------------------------|-----------------------|---------|
| PLOFLON PTFE GLASS FABRIC | Tear-Resistance Serie | PTFE    |

Specialty formulated PLOFLON PTFE coating provide more flexibility and improve tear resistance. These fabrics are typically used in applications requiring high-flex properties.

| Properties                                    | Value                 | Unit              |
|---|-----------------------|-------------------|
| Standard width<br>Please ask for other widths | 7, 10, 20, 30, 40, 50 | mm                |
| Thickness                                     | 0,075                 | mm                |
| Weight  | 135                   | gr/m <sup>2</sup> |
| PTFE Content                                  | 64                    | %                 |
| Tensile strenght                              | 980                   | N/5 cm            |
| Temperature resistance                        | -150° / +260°         | Celsius           |
| Roll standard length:                         | 30                    | m                 |

**Note:** Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m<sup>2</sup> = ±%5

All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained herein are based on test results PLOFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.

REF10808TR30122015