

PLOFLON Polyester Klebeband mit Silikonkleber



Product	Product category	Coating
---------	------------------	---------

Polyester Tape green
Self adhesive

Premium Serie

Silicone

PLOFLON Premium Series, a polyester film coated on one side with a crosslinked silicone adhesive.

This is by far the most used tape for the powder coat industry. General purpose high temperature splicing tape. High temperature masking tape for powder coating and other applications.

Suitable for use as a flash breaker tape in the aerospace industry. Also used as a high temperature photo splicing tape for attaching film to leader card on all automatic photo developing and printing machines.

Properties	Value	Unit
Standard width Please ask for other widths	9, 12, 20, 30, 40, 50	mm
Roll Length	66	m
Film thickness	50	my
Adhesive Thickness	40	my
Total Thickness	90	my
Tensile	50	lbs./in.
Adhesion to Steel:	26	oz./in.
Elongation	110 % at break
Temperature	max 210°	up to 210°C

Note: Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m² = ±%5

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.