

PLOFLON® special PTFE-tape with silicone adhesive



Product	GdYUJ Product category	Coating
PLOFLON® special PTFE GLASS FABRIC Self wound adhesive tape	Premium Serie	Silicone PSA

PLOFLON® special PTFE-tapes is used by packaging industry as a release surface on heat sealers, blister formation and form-fill-seal equipment. The anti-stick and durability properties of the PLOFLON® special PTFE-tape makes it a perfect product for the lining of guide slides, chutes and rails. The high temperature resistant and non-stick properties allow it to perform as an excellent release surface in the composite industry. Easy-release surface on packaging and heat sealing machines, ironing and pressing equipment.

Properties	Value	Unit
Standard width <small>Please ask for other widths 3</small>	300mm - Article SW10141	
	355mm - Article SW10141.1	
	460mm - Article SW10141.2	
	500mm - Article SW10141.3	
Total thickness	0,120	mm
Tensile strength	450	N/5cm
Adhesion	ca. 5,90	N/cm
Temperature resistance	-73° / +260°	Celsius
Roll length:	10mm	m
Elongation	< 5	%
Colour	Brown	

Note: Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m² = ±%5

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON® believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.