

PLOFLON Teflon film as cutting goods



Product	Product category	Coating
---------	------------------	---------

PLOFLON PTFE GLASS FABRIC
Self adhesive or not adhesive

Premium Serie

If self adhesive then Silicone PSA

PLOFLON Premium Series
PTFE/glass fabrics coated on one side with high temperature pressure sensitive silicone adhesive. Yellow textured PVC release liner is applied to the adhesive surface for ease of application.

Some application: Easy release surface on heat sealing and packaging machines, ironing and pressing equipment, covering drying cylinders, lining chutes, release surface on bonding tools.

Properties	Value	Unit
standard dimensions Please ask for other dimensions	200 x 500, 300 x 500, 400 x 500, 500 x 500, 600 x 500, 700 x 500, 800 x 500, 900 x 500, 1000 x 500	mm
Backing thickness without silicone adhesive	approximately 0,130	mm
Total thickness if with silicone adhesive	approximately 0,175	mm
Backing weight	approximately 255 / 296	gr/m ²
Adhesion if with silicone adhesive	5,40	N/cm
Temperature resistance	-73° / +260°	Celsius
Minimum order	2	piece

Note: Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m² = ±5%

All technical data are based on average values. The values are not intended for use in preparing specifications. Technical information contained here is based on test results PLOFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.