

# PLOFLON Teflon® Klebeband mit Acrylkleber



Product	Product category	Coating
PLOFLON Glass Cloth Self Adhesive Tape	Adhesive Tape Serie	ACRYLC

PLOFLON Fiberglass cloth tape coated with a acrylic pressure sensitive adhesive for many applications requiring high temperature resistance, high adhesion and a very strong abrasion-resistant backing. Applications include electrical insulation, coil and motor wrappings, protective wrapping for wire and cables, light duty plasma or flame spray masking tape and general industrial applications.

Properties	Value	Unit
Standard width <b>Please ask for other widths</b>	10, 20, 30, 40, 50	mm
Thickness	0,120mm	mm
Total Thickness	0,180mm	mm
Adhesion	4,0	N/cm
Tensile strenght	1000	N/5 cm
Temperature resistance	-40 / +150°	Celsius
Elongation	4,4	%

**Note:** Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m<sup>2</sup> = ±%5

All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained herein are based on test results PLOFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.

REFF462A18022016