

# PLOFLON Teflon film - adhesive with acrylic adhesive



Product	Product category	Coating
---------	------------------	---------

PLOFLON PTFE GLASS FABRIC  
Self adhesive

Premium Serie

Acrylic adhesive

PLOFLON Premium Acrylic Series  
PTFE/glass fabrics coated on one  
side with acrylic pressure sensitive..  
Smooth blue PE liner is applied to the  
adhesive surface for ease application.

Some application: Easy release  
surface on heat sealing and  
packaging machines, ironing and  
pressing equipment, covering drying  
cylinders, lining chutes, release  
surface on bonding tools.

Properties	Value	Unit
Standard width <small>Please ask for other widths</small>	1000	mm
Backing thickness	0,125 / 0,140	mm
Total thickness	0,175 / 0,190	mm
Backing weight	255 / 296	gr/m <sup>2</sup>
Adhesion	4,00	N/cm
Temperature resistance	-40° / +170°	Celsius
Roll length:	from 1 m to 30 m Standard roll length 30 m	m

**Note:** Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum. Weight Tolerance g/m<sup>2</sup> = ±%5

All technical data are based on average values. The se values are not intended for use in preparing specifications. Technical information contained here in are based on test results PLOFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.